# Chemical Safety Data Sheet MSDS / SDS

# Acetaldehyde

Revision Date: 2025-02-01 Revision Number: 1

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **Product identifier**

Product name : Acetaldehyde

CBnumber : CB8175809

CAS : 75-07-0

EINECS Number : 200-836-8

Synonyms : acetaldehyde,Formaldehyde solution

## Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.

Uses advised against : none

## **Company Identification**

Company : Chemicalbook

Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing

Telephone : 400-158-6606

## SECTION 2: Hazards identification

## GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word Danger

## Precautionary statements

P201 Obtain special instructions before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

 $P303 + P361 + P353 \; \text{IF ON SKIN (or hair)}: \; Remove/Take \; off \; Immediately \; \text{all contaminated clothing}. \; Rinse \; SKIN \; \text{with water/shower}.$ 

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continuerinsing.

P337+P313 IF eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use ... for extinction.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

## Hazard statements

H224 Extremely flammable liquid and vapour

H225 Highly Flammable liquid and vapour

H302 Harmful if swallowed

H319 Causes serious eye irritation

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

H351 Suspected of causing cancer

#### Disposal

WARNING.Cancer - https://oehha.ca.gov/proposition-65/chemicals/acetaldehyde

# SECTION 3: Composition/information on ingredients

#### **Substance**

Product name : Acetaldehyde

Synonyms : acetaldehyde,Formaldehyde solution

CAS : 75-07-0

EC number : 200-836-8

MF : C2H4O

MW : 44.05

## SECTION 4: First aid measures

## Description of first aid measures

## General advice

Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Call in physician.

## In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

## In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

## If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

## Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

## Indication of any immediate medical attention and special treatment needed

No data available

# SECTION 5: Firefighting measures

## **Extinguishing media**

#### Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

#### Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

## Special hazards arising from the substance or mixture

Carbon oxides Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.

## Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.


## **Further information**

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

## **NFPA 704**

**FIRE** 

REACT



Intense or continued but not chronic exposure could cause temporary incapacitation or possible residual injury (e.g. <u>diethyl</u> HEALTH 2 <u>ether</u>, ammonium phosphate, iodine)

Will rapidly or completely vaporize at normal atmospheric pressure and temperature, or is readily dispersed in air and will 4 burn readily. Includes pyrophoric substances. Flash point below room temperature at 22.8 °C (73 °F). (e.g. acetylene, propane, hydrogen gas)

Undergoes violent chemical change at elevated temperatures and pressures, reacts violently with water, or may form explosive mixtures with water (e.g. white phosphorus, potassium, sodium)

SPEC.

HAZ.

## SECTION 6: Accidental release measures

## Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

## **Environmental precautions**

Do not let product enter drains. Risk of explosion.

## Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquidabsorbent material (e.g.

Chemizorb?). Dispose of properly. Clean up affected area.

## Reference to other sections

For disposal see section 13.

# SECTION 7: Handling and storage

## Precautions for safe handling

## Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

## Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

## Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

## Conditions for safe storage, including any incompatibilities

## Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

## Storage stability

Recommended storage temperature 2 - 8 °C

## Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# SECTION 8: Exposure controls/personal protection

## control parameter

## Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

## **Exposure controls**

#### Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate

government standards such as NIOSH (US) or EN 166(EU). Safety glasses Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0,7 mm Break through time: 480 min Material tested:Butoject? (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact Material: butyl-rubber

Minimum layer thickness: 0,7 mm Break through time: 480 min Material tested:Butoject? (KCL 898)

**Body Protection** 

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: Filter type AX

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

#### **Exposure limits**

TLV-TWA 180 mg/m<sup>3</sup> (100 ppm) (ACGIH), 360 mg/m<sup>3</sup> (200 ppm) (NIOSH); STEL 270 mg/m<sup>3</sup> (150 ppm); IDLH 10,000 ppm.

# SECTION 9: Physical and chemical properties

## Information on basic physicochemical properties

Appearance colorless liquid, clear

| Odour                                   | pungent   |
|---|---|
| Odour Threshold                         | 0.0015ppm   |
| рН                                      | 5 at 20 °C  |
| Melting point/freezing point            | Melting point: -123,5 °C  |
| Initial boiling point and boiling range | 21 °C at 1.013 hPa  |
| Flash point                             | -38,89 °C - closed cup  |
| Evaporation rate                        | No data available   |
| Flammability (solid, gas)               | No data available   |
| Upper/lower flammability or explosive   | Upper explosion limit: 57 %(V) Lower explosion limit: 4 %(V)                    |
| limits                                  |   |
| Vapour pressure                         | 1.202 hPa at 25 °C  |
| Vapour density                          | 1,52 - (Air = 1.0)  |
| Relative density                        | 0.823 (20/4℃) (?90% Soln.)  |
| Water solubility                        | completely miscible   |
| Partition coefficient: n-octanol/water  | log Pow: 0,63 - Bioaccumulation is not expected.                                |
| Autoignition temperature                | 175 °C at 1.013 hPa   |
| Decomposition temperature               | No data available   |
| Viscosity                               | Viscosity, kinematic: No data available Viscosity, dynamic: 0,24 mPa.s at 20 °C |
| Explosive properties                    | No data available   |
| Oxidizing properties                    | No data available   |
| Henry's Law Constant                    | 7.69 at 25 °C (Snider and Dawson, 1985:Benkelberg et al., 1995)                 |
| •                                       |   |

## Other safety information

Relative vapor density

1,52 - (Air = 1.0)

# SECTION 10: Stability and reactivity

## Reactivity

Vapors may form explosive mixture with air.

## **Chemical stability**

The product is chemically stable under standard ambient conditions (room temperature) . Avoid exposure to air any longer than necessary so as to prevent peroxide formation.

Stable under recommended storage conditions.

## Possibility of hazardous reactions

No data available

## **Conditions to avoid**

Warming.

## Incompatible materials

## Hazardous decomposition products

In the event of fire: see section 5

# **SECTION 11: Toxicological information**

## Information on toxicological effects

## **Acute toxicity**

Oral

#### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation (OECD Test Guideline 404)

## Serious eye damage/eye irritation

Eyes - Rabbit

Result: Severe irritations Remarks: (RTECS)

Lacrimal irritation due to vapours. conjunctivitis

## Respiratory or skin sensitization

No data available

#### Germ cell mutagenicity

Suspected of causing genetic defects. Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium Metabolic activation: with and without metabolic activation Result: negative

Remarks: (ECHA)

## Carcinogenicity

No data available

## Reproductive toxicity

No data available

## Specific target organ toxicity - single exposure

May cause respiratory irritation.

## Specific target organ toxicity - repeated exposure

No data available

#### **Aspiration hazard**

No data available

## **Toxicity**

LD50 orally in rats: 1930 mg/kg (Smyth)

# SECTION 12: Ecological information

## **Toxicity**

## Toxicity to fish

static test LC50 - Pimephales promelas (fathead minnow) - 31 mg/l

- 96 h

Remarks: (ECHA)

#### Toxicity to daphnia and other aquatic invertebrates

static test EC50 - Daphnia magna (Water flea) - ca. 48,3 mg/l - 48 h Remarks: (ECHA)

#### Toxicity to algae

static test ErC50 - Pseudokirchneriella subcapitata - > 100 mg/l - 72 h

(OECD Test Guideline 201)

static test EC10 - Pseudokirchneriella subcapitata - > 100 mg/l - 72 h

(OECD Test Guideline 201)

## Persistence and degradability

Biodegradability aerobic Biochemical oxygen demand - Exposure time 14 d Result: 80 % - Readily biodegradable.

(OECD Test Guideline 301C)

## **Bioaccumulative potential**

No data available

## Mobility in soil

No data available

## Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at

levels of 0.1% or higher.

## **Toxics Screening Level**

The Initial Threshold Screening Level for acetaldehyde is 9 µg/m3 with an annual averaging time (AT).

## Other adverse effects

No data available

# SECTION 13: Disposal considerations

## Waste treatment methods

#### Incompatibilities

Reacts with air to form unstable peroxides which can explode. Contact with air causes acetaldehyde to chemically degrade to acetic acid.

Strong oxidizers, acids, bases, alcohols, ammonia, amines, halogens, phenols, acid anhydrides, ketones, hydrogen cyanide, hydrogen sulfide.

## **Product**

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

## Waste Disposal

Consult with environmental regulatory agencies for guidance on acceptable disposal practices. Generators of waste containing this contaminant (≥100 kg/mo) must conform with EPA regulations governing storage, transportation, treatment, and waste disposal. Incineration.

# **SECTION 14: Transport information**

## **UN** number

ADR/RID: 1089 IMDG: 1089 IATA: 1089

**UN proper shipping name** 

ADR/RID: ACETALDEHYDE IMDG: ACETALDEHYDE IATA: Acetaldehyde

Passenger Aircraft: Not permitted for transport

Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

**Packaging group** 

ADR/RID: I IMDG: I IATA: I

**Environmental hazards** 

ADR/RID: no IMDG Marine pollutant: no IATA: no

Special precautions for user

No data available

## **SECTION 15: Regulatory information**

## Safety, health and environmental regulations/legislation specific for the substance or mixture

## Regulations on the Safety Management of Hazardous Chemicals

China Catalog of Hazardous chemicals 2015:Listed. website: https://www.mem.gov.cn/

## Measures for Environmental Management of New Chemical Substances

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC):Listed. website: https://www.mee.gov.cn/

EC Inventory:Listed.

 $\label{lem:commercial} \mbox{European Inventory of Existing Commercial Chemical Substances (EINECS): Listed. website: $$https://echa.europa.eu/$$$ 

Korea Existing Chemicals List (KECL):Listed. website: http://ncis.nier.go.kr

New Zealand Inventory of Chemicals (NZloC):Listed. website: https://www.epa.govt.nz/

Philippines Inventory of Chemicals and Chemical Substances (PICCS):Listed. website: https://emb.gov.ph/

United States Toxic Substances Control Act (TSCA) Inventory:Listed. website: https://www.epa.gov/

Vietnam National Chemical Inventory:Listed. website: https://chemicaldata.gov.vn/

## SECTION 16: Other information

## Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS: Chemical Abstracts Service

EC50: Effective Concentration 50%

IATA: International Air Transportation Association

IMDG: International Maritime Dangerous Goods

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

STEL: Short term exposure limit TWA: Time Weighted Average

## References

[1] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple

[2] ChemlDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp

[3] ECHA - European Chemicals Agency, website: https://echa.europa.eu/

[4] eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:

http://www.echemportal.org/echemportal/index?pageID=0&request\_locale=en

[5] ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: http://www.phmsa.dot.gov/hazmat/library/erg

[6] Germany GESTIS-database on hazard substance, website: http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp

[7] HSDB - Hazardous Substances Data Bank, website: https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm

[8] IARC - International Agency for Research on Cancer, website: http://www.iarc.fr/

[9] IPCS - The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home

[10] Sigma-Aldrich, website: https://www.sigmaaldrich.com/

#### Other Information

Depending on the degree of exposure, periodic medical examination is suggested. The occupational exposure limit value should not be exceeded during any part of the working exposure. An added stabilizer or inhibitor can influence the toxicological properties of this substance; consult an expert. Rinse contaminated clothing with plenty of water because of fire hazard.

#### Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.