

Chemical Safety Data Sheet MSDS / SDS

Styrene

Revision Date:2025-02-01 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : Styrene
CBnumber : CB3415111
CAS : 100-42-5
EINECS Number : 202-851-5
Synonyms : styrene,Sm

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 400-158-6606

SECTION 2: Hazards identification

GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word

Danger

Precautionary statements

P405 Store locked up.

P311 Call a POISON CENTER or doctor/physician.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continuerinsing.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P201 Obtain special instructions before use.

Hazard statements

H372 Causes damage to organs through prolonged or repeated exposure

H370 Causes damage to organs

H361 Suspected of damaging fertility or the unborn child

H332 Harmful if inhaled

H319 Causes serious eye irritation

H315 Causes skin irritation

H226 Flammable liquid and vapour

H225 Highly Flammable liquid and vapour

Disposal

WARNING.Cancer - <https://oehha.ca.gov/proposition-65/chemicals/styrene>

SECTION 3: Composition/information on ingredients

Substance

Product name	: Styrene
Synonyms	: styrene,Sm
CAS	: 100-42-5
EC number	: 202-851-5
MF	: C ₈ H ₈
MW	: 104.15

SECTION 4: First aid measures

Description of first aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

If breathing stops: immediately apply artificial respiration, if necessary also oxygen.After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Carbon oxides

Container explosion may occur under fire conditions., Vapors may form explosive mixture with air.

Mixture with combustible ingredients.

Vapors are heavier than air and may spread along floors. Risk of dust explosion.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.


Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

NFPA 704



■ HEALTH	2	Intense or continued but not chronic exposure could cause temporary incapacitation or possible residual injury (e.g. diethyl ether , ammonium phosphate, iodine)
■ FIRE	3	Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions . Liquids having a flash point below 22.8 °C (73 °F) and having a boiling point at or above 37.8 °C (100 °F) or having a flash point between 22.8 and 37.8 °C (73 and 100 °F). (e.g. gasoline, acetone)
■ REACT	2	Undergoes violent chemical change at elevated temperatures and pressures, reacts violently with water, or may form explosive mixtures with water (e.g. white phosphorus, potassium , sodium)

SPEC.

☐ HAZ.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

Environmental precautions

Do not let product enter drains. Risk of explosion.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g.

Chemisorb?). Dispose of properly. Clean up affected area.

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Storage stability

Recommended storage temperature 2 - 8 °C

Light sensitive.

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

control parameter

Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: Filter type ABEK

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

Exposure limits

TLV-TWA 50 ppm ($\sim 212 \text{ mg/m}^3$) (ACGIH and NIOSH), 100 ppm ($\sim 425 \text{ mg/m}^3$) (OSHA and MSHA); ceiling 200 ppm, peak 600 ppm/5 min/3 h (OSHA); STEL 100 ppm ($\sim 425 \text{ mg/m}^3$) (ACGIH).

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

Appearance	liquid
Odour	No data available
Odour Threshold	0.035ppm
pH	No data available
Melting point/freezing point	-31 °C (lit.)
Initial boiling point and boiling range	145-146 °C (lit.)
Flash point	32,0 °C - closed cup

Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	1.1-8.9%(V)
Vapour pressure	12.4 mm Hg (37.7 °C)
Vapour density	3.6 (vs air)
Relative density	0.909
Water solubility	0.24g/l
Partition coefficient: n-octanol/water	No data available
Autoignition temperature	No data available
Decomposition temperature	No data available
Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
Explosive properties	No data available
Oxidizing properties	No data available
Henry's Law Constant	($\times 10^{-3}$ atm·m ³ /mol): 3.91 at 25 °C (static headspace-GC, Welke et al., 1998)

Other safety information

No data available

SECTION 10: Stability and reactivity

Reactivity

Vapor/air-mixtures are explosive at intense warming.

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

No data available

Conditions to avoid

Heating.

Incompatible materials

Strong oxidizing agents

Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Oral

Inhalation: No data available Dermal

Skin corrosion/irritation

Mixture causes skin irritation.

Serious eye damage/eye irritation

Mixture causes serious eye irritation.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

Evidence of harm to the unborn child.

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Mixture causes damage to organs through prolonged or repeated exposure.

No data available

Toxicity

LD50 in mice (mg/kg): 660 ± 44.3 i.p.; 90 ± 5.2 i.v.

SECTION 12: Ecological information

Toxicity**Mixture**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Toxics Screening Level

The Initial Threshold Screening Level (ITSL) is 1000 µg/m³ with an annual averaging time.

Other adverse effects

No data available

Components styrene

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead

Toxicity to daphnia and other aquatic invertebrates

minnow) - 10 mg/l - 96 h (OECD Test Guideline 203)

flow-through test EC50 - Daphnia magna (Water flea) - 4,7 mg/l - 48 h

(OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata (green algae) - 4,9 mg/l - 72 h

Toxicity to bacteria static test EC50 - activated sludge - 500 mg/l - 30 min (OECD Test Guideline 209)

SECTION 13: Disposal considerations

Waste treatment methods

Incompatibilities

Styrene May form explosive mixture with air. Before entering confined space where this chemical may be present, check to make sure that an explosive concentration does not exist. Store in a cool, dry area away from oxidizers, catalysts for vinyl polymers; peroxides, strong acids; aluminum chloride.

Product

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

Waste Disposal

Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. All federal, state, and local environmental regulations must be observed. In some cases, recovery and recycle of styrene monomer is economic and the technology is available.

SECTION 14: Transport information

UN number

ADR/RID: 2055 IMDG: 2055 IATA: 2055

UN proper shipping name

ADR/RID: STYRENE MONOMER, STABILIZED IMDG: STYRENE MONOMER, STABILIZED

IATA: Styrene monomer, stabilized

14.3 Transport hazard class(es)

ADR/RID: 3 IMDG: 3

IATA: 3

14.4 Packaging group

ADR/RID: III IMDG: III

IATA: III

14.5	Environmental hazards	
	ADR/RID: no IMDG Marine pollutant: no	IATA: no
14.6	Special precautions for user	
	No data available	

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations on the Safety Management of Hazardous Chemicals

China Catalog of Hazardous chemicals 2015: Listed. website: <https://www.mem.gov.cn/>

Measures for Environmental Management of New Chemical Substances

Philippines Inventory of Chemicals and Chemical Substances (PICCS): Listed. website: <https://emb.gov.ph/>

Korea Existing Chemicals List (KECL): Listed. website: <http://ncis.nier.go.kr>

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC): Listed. website: <https://www.mee.gov.cn/>

New Zealand Inventory of Chemicals (NZIoC): Listed. website: <https://www.epa.govt.nz/>

European Inventory of Existing Commercial Chemical Substances (EINECS): Listed. website: <https://echa.europa.eu/>

United States Toxic Substances Control Act (TSCA) Inventory: Listed. website: <https://www.epa.gov/>

Vietnam National Chemical Inventory: Listed. website: <https://chemicaldata.gov.vn/>

EC Inventory: Listed.

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

References

【1】 CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>

【2】 ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>

【3】 ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

【4】 eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:

http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en

【5】 ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>

【6】 Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>

- 【7】 HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>
- 【8】 IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>
- 【9】 IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>
- 【10】 Sigma-Aldrich, website: <https://www.sigmaaldrich.com/>

Other Information

Depending on the degree of exposure, periodic medical examination is suggested. Check for peroxides prior to distillation; eliminate if found. Styrene monomer vapours are uninhibited and may form polymers in vents or flame arresters of storage tanks, resulting in blockage of vents. Do NOT take working clothes home.

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.